

imagePROGRAF

Lei Series

SCAN-TO-COPY/FILE/CLOUD



TECHNICAL DOCUMENTS

MFP LARGE-FORMAT IMAGING

Introducing the new, entry-level Multifunction Printers: the imagePROGRAF TM-300 MFP L36ei, TM-200 MFP L24ei, iPF770 MFP L36ei, and iPF670 MFP L24ei Large-Format MFP systems

Affordable and easy-to-use, scan-to-copy/file/cloud Multifunction Printer (MFP) solutions

Designed for the low-volume and entry-level user, these MFP solutions offer user-friendly, scan-to-copy/file/ cloud solutions for architects, engineers, consulting firms, small offices, and K-12 schools that require a minimal learning curve when it comes to new equipment.

FEATURES

Scanner

- The 36" L36ei scanner weighs approx. 14.5 lb. and the 24" L24ei scanner weighs approx. 11.6 lb.; both are lightweight and compact
- Intuitive touch screen with easy-to-identify picture identification functions
- SingleSensor Scanning Technology

• Fast first-copy-out time

Simple Operation

- "Green Button" scan-to-copy functionality
- No PC required

Easy Installation

- Scanner is easily integrated with the printer
- Compact MFP takes up minimal office space Printer
- TM-300 36" and TM-200 24" pigment ink models
- iPF770 36" and iPF670 24" dye/pigment ink models

imagePROGRAF

At a low cost, small office environments and schools can now afford an MFP. **SCANNER** SOFTWARE AVAILABLE PRINTER

These scanners, utilizing SingleSensor Technology,* have simple, integrated control panels that allow users to operate the scanner with a simple push of a button. This technology helps provide consistent and better color accuracy with more detail in the shadows and highlights than a staggered CIS array scanner.

Scan-to-Copy

- Three quality modes: Draft, Standard, and Best
- Settings include Auto Crop Borders, Number of Copies, Brightness, Black Point, and White Point
- Optical resolution of up to 600 dpi
- Media thickness up to .5 mm
- Scan single documents into a multipage PDF

Scan-to-USB Thumb Drive

- TIFF file format
- TIFF, JPEG, PDF, PDF/A, and Multipage PDF files formats (via ScanApp Lei)

Scan-to-ScanApp Lei (PC only)**

• TIFF, JPEG, PDF, PDF/A, and Multipage PDF file formats

With the option of a 36" or 24" pigment ink printer or a 36" or 24" dye/pigment ink printer, you now have the ability to choose the printer that best fits your needs.

TM-300 MFP L36ei/TM-200 MFP L24ei

- 5-color TD Pigment Ink System
- Security solutions
- Color, touch-screen operation panel on the printer
- iPF770 MFP L36ei /iPF670 MFP L24ei
- 5-color dye/pigment reactive ink system
- 130 ml ink tanks
- Economy Print mode

Direct Print & Share: † Canon's cloud portal solution allows for the sharing and batch printing of JPEG, TIFF, PDF, and HP-GL/2 files from almost anywhere in the world. Shortcut printing capability has been added for drag-and-drop printing as well as scan-to-cloud capabilities.

PosterArtist Lite: Poster creation software gives you all the tools needed to design and output impressive, largeformat signs and banners (PC only).

Print Plug-in for Microsoft[®] Office: Allows for users of any skill level to print posters or banners directly from Microsoft® Excel®, PowerPoint[®], and Word.

Accounting Manager: This management tool easily helps track costs and allocate consumable expenses to projects. It also allows you to track print jobs by user to calculate ink and media (PC only).

Free Layout Plus: New! Nest, tile, and create custom layouts before printing your files with this print utility. Use the Plug-in feature to print directly from Microsoft office programs. Compatible with the TM-300 and TM-200 models only.



* SingleSensor Technology Assembly means that multiple sensors are contained in one assembly device

** Minimum PC specification: Windows 7/8 - 32-bit/Intel Celeron, Core-Duo, Core-2-Duo or 2.8 GHz Hyper-Threading (HT) or AMD Dual-Core processors/2 GB RAM/High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2 GB for applications and 20 GB free for images.

⁺ Direct Print & Share comes embedded with the imagePROGRAF TM-300 MFP L36ei, TM-200 MFP L24ei, iPF770 MFP L36ei, and iPF670 MFP L24ei large-format printers, and is also available as a free download at usa.canon.com/downloads. You must sign up for the Google[™] service separately. This service is subject to Google's terms and conditions. Based on Google's current services. Subject to change at Google's discretion. Note: The imagePROGRAF MFP Lei systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings

SPECIFICATIONS

TM-300/200 PRINTER Print Head PF-06 Ink Type **Pigment**: Cyan (C), Magenta (M), Yellow (Y), Black (BK), Matte Black (MBK) Ink Tank PFI-120 (130 ml): C, M, Y, BK, MBK PFI-320 (300 ml): C, M, Y, BK, MBK Ink Tank Capacity Starter: MBK (130 ml), BK, C, M, Y (90 ml) Replacement: 130 ml or 300 ml Ink Supply Method Tubing System with Sub-ink Tanks for Continuous Ink Supply Media Thickness 0.07 - 0.8 mm (2.8 - 31.4 mil) Media Core Sizes 2" and 3" Core (Adapter Included) Maximum Roll Outer Diameter 5.9" (150 mm) **Output Media Bin** Basket Printing Software imagePROGRAF Printer Driver for Windows®/Mac®, Optimized Module for AutoCad® for Windows, Direct Print & Share (PC only), Media Configuration Tool, PosterArtist Lite for Windows, Accounting Manager, Apple AirPrint, Free Layout Plus, Device Management Console, Canon Print Service, Canon PRINT Inkjet, Selphy, Easy Photo Print Editor*** **Operating System** Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12x Print Language SG Raster (Canon Proprietary), HP-GL/2, HP RTL, JPEG Interface USB 2.0 Hi-speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n) Dimensions (H × W × D) and Weight (with Stand and Basket) TM-300 41.8"x 51"x 34.3" (SD-31: with basket open) Weight: 130 lb. (SD-31, roll holder included, no inks, no print heads) TM-200 41.8" x 38.7" x 34.3" (SD-22: with basket open) Weight: 112 lb. (SD-22, roll holder included, no inks, no print heads) User Replaceable Items Ink Tank (PFI-120/PFI-320) Print Head (PF-06) Maintenance Cartridge (MC-31) Cutter Blade (CT-08) iPF770/670 PRINTER Print Head

PF-04

Ink Type

Dye: Cyan (C), Magenta (M), Yellow (Y), Black (BK) Pigment: Matte Black (MBK) Ink Tank

PFI-107: C, M, Y, BK, MBK

imagePROGRAF Lei Series

Maximum Scan Length Starter: 90 ml; Replacement: 130 ml 109' Maximum Media Thickness Tubing System with Sub-ink Tanks for Continuous 0.020" (.5 mm) Digital Imaging Technology Contact Image Sensor (CIS) Technology 0.07 - 0.8 mm (2.8 - 31.4 mil) (SingleSensor Technology Assembly) • Full width SingleSensor CIS Assembly 2" and 3" Core (Adapter Included) • 24-bit RGB digital color image capture Maximum Roll Outer Diameter 8-bit grayscale image capture · Panchromatic monochrome and black and white · Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability imagePROGRAF Printer Driver for Windows*/Mac*, Scanner Interface Printer Driver Extra Kit for Windows/Mac Scan to USB - USB2 interface [Free Layout, Color imageRUNNER® Enlargement (Flash drive max. size = 128 GB - FAT32) Copy (PC only), Advanced Preview], Print Plug-in Copy/Scan to Network - Ethernet interface for Microsoft Office (PC only), Optimized Module (>1 GB Ethernet connection for network configuration) for AutoCad[®] for Windows, Direct Print & Share **Operating Environments** (PC only), Status Monitor for Windows, 10 - 35°C, 35-80% RH, Non-condensing Print Monitor for Mac, Media Configuration Tool, PosterArtist Lite for Windows External Power Supply 100-240 VAC Autosensing +/- 10%, 50-60 Hz Windows XP (32-bit), Server 2003 (32/64-bit), Scanner Power Consumption Server 2008 (32/64-bit), Server 2012, (64-bit), • 11.7 W (Scanning) Windows Vista[®] (32/64-bit), Windows 7 (32/64-bit), • .06 W (Standby) Windows 10 (32/64-bit), Macintosh OS X 10.6.8-10X Compliances CB, CE, FCC, UL, ENERGY STAR®, ICES-003, CUL, S Mark GARO (Canon Proprietary), HP-GL/2, HP RTL Dimensions (H x W x D) (with Paper Tray Extended) L36ei: 5.2" x 48.7" x 9.96" USB 2.0 Hi-Speed, 10/100/1000Base-T/TX L24ei: 5.2" x 36.8" x 9.96" Dimensions (H × W × D) and Weight (with Stand and Basket) Stand and Scanner Weight L36ei: Approx.14.5 lb. 42" x 51" x 34" (ST-33: with basket open) L24ei: Approx. 11.6 lb. Weight: 155.2 lb. (ST-33, roll holder included, no inks, What's In The Box? • Lei Scanner with Power Cord 42"x 39"x 34" (ST-26: with basket open) • Ethernet Cable Weight: 128.2 lb. (ST-26, roll holder included, no inks, 2 Mounting Brackets • CD for ScanApp Lei Software • Lei Scanner Guide Ink Tank (PFI-107 MBK, BK, C, M, Y) • Document Return Guide Calibration Target • Feet for Desktop Use • Two Paper Edge Guides and Paper Refeed Preventers * The scan rate is proportional across the full range of resolutions supported by the scanner. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types ** The quoted scan accuracy may vary depending on the operating environment and the thickness of the media. *** To be supported in December 2018. Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients. ScanApp Lei not available on Mac. The imagePROGRAF MFP Lei systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability





As an ENERGY STAR partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imagePROGRAF, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. iPad is a registered trademark of Apple Inc. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors ©2018 Canon U.S.A., Inc. All rights reserved.

0214W461 0918-LeiBrochure-7.5M-PIH







with respect to such third-party offerings.



- Color Space
 - Resolution
 - 600 dpi (optical)

 - L36ei: 36"; L24ei: 24"
 - Maximum Media Width

Scan Modes

Ink Tank Capacity

Ink Supply Method

Ink Supply

Media Thickness

Media Core Sizes

Output Media Bin

Printing Software

Operating System

Print Language

iPF770

iPF670

no print heads)

no print heads)

User Replaceable Items

Interface

Basket

5.9" (150 mm)

- Scan Accuracy
- Maximum Image Width

- Print Head (PF-04) Maintenance Cartridge (MC-10) Lei SERIES SCANNER Scan Speed* 24-bit Full Color @ 200 dpi: 1" per second 8-bit Grayscale and Monochrome @ 200 dpi: 3" per second
 - 16.7-million Color RGB (24-bit)

- L36ei: 38"; L24ei: 26"
- 256-level Grayscale (8-bit) Black and White (1-bit) Normalized RGB
- +/-0.2%